

Notes:

- This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) 11/8".

PARCEL PL5 17" H x 12" W x 15" D 2
PARCEL PL6 20-1/2" H x 12" W x 15" D 2

VERSATILE™ 4C FRONT LOAD MAILBOX

FIORENCE manufacturing company

PRODUCT SERIES:

5935 Corporate Drive • Manhattan, KS 66503 www.florencemailboxes.com • (800) 275-1747 A GIBRALTAR INDUSTRIES COMPANY

	MODEL 4C11D-4P	REV	С
,	SCALE NONE	LAST REV DATE 5/15/14	
3	DRAWING NUMBER		RAWN BY
17	4C11D-4PCS		RS