J.S. MAIL SUPPLY versatileTM 4C Mailbox, 4C16D-6P 262-782-6510 Toll Free: 800-571-0147 1553 E. Racine Ave. Waukesha, WI 53186 17" R.O. 31 9/16" ACTUAL **DEPTH** 30 5/8" MAX R.O. 30 3/8" MIN 56 1/2" 55 7/8" MAX R.O. 55 5/8" MIN **ACTUAL** 63 1/2" (TO TENANT ຸດ ເ ເ ເ ເ LOCK) 15" 14 1/8" (TO BOTTOM FROM FINISHED FLOOR SHELF) TO BOTTOM OF R.O.

FINISHED FLOOR

COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
PARCEL	PL15	15" H x 12" W x 15" D	2
PARCEL	PL5	17" H x 12" W x 15" D	2
PARCEL	PL6	20-1/2" H x 12" W x 15" D	2

Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX



5935 Corporate Drive • Manhattan, KS 66503 800.275.1747 • www.florencemailboxes.com

MODEL 4C16D-6P		REV	Е
SCALE	NONE	LAS	T REV DATE 1/13/2021
DRAWING	NUMBER		DRAWN BY
4C	16D-6PCS		RAK